

## EL2326 Series

OAM Managed 10/100/1000BASE-TX to 100/1000BASE-X Dual Rate Media Converter



## Overview

**This product is discontinued as of 1st October 2020. [click here](#) for alternative product.**

The EL2326 Series provides media conversion between 10/100/1000BASE-T(X) and 100-FX Fiber or 1000BASE-SX/LX Fiber. EL2326's fiber design is compatible to 100BASE fiber or 1000BASE fiber transceiver.

The EL2326 managed media converter supports Telnet, SNMP v1/v2, and web browser management, enabling value-added connectivity and bandwidth control. Key features include; IEEE802.3ah OAM compliance, VLAN tagging, broadcast storm protection, Far-End-Fault, and Link-Fault-Pass-Through resulting in reliable communications between networks.

With link down alarming and a wide range of fiber connectivity options, the EL2326 is the ideal managed media converter for industrial environments where connectivity is crucial.

EtherWAN — "When Connectivity is Crucial."

## Spotlight

### Gigabit Connectivity

- » Auto 10/100/1000BASE-T X and 1000BASE-SX/LX/BX Ethernet transmission conversion
- » 1000Mbps Full duplex, 10/100Mbps Full/Half duplex
- » Fiber interface supports dual rate 100BASE-FX and 1000BASE-SX/LX fiber transmission

### Managed Functions

- » Supports IEEE 802.3ah OAM standards
- » Supports SNMPv1, SNMPv2
- » Supports bandwidth control and VLAN base priority tag

### Built-in Fiber Tray

## Features

### Management

- » Interface
    - Web Browser
    - SNMP v1/v2c/v3
  - » Firmware and configuration upgrade and backup via TFTP
  - » Supports DHCP Server/Client
  - » RMON (Remote monitoring): group 1, 2, 3, 9
- 

### Security

- » MAC Address by port security
  - » Enable/disable port
  - » Storm control (broadcast and multicast types)
  - » IEEE802.1x LAN access control
  - » Remote authentication through RADIUS
  - » SSL for web security
- 

### Quality of Service (QoS)

- » Priority Queues: 4 queues per port
  - » Traffic classification based on IEEE802.1p CoS, DSCP, WRR (Weighted round robin)
  - » Rate Limiting (Ingress/Egress)
- 

### Layer 2 Features

- » Auto-negotiation for port speed and duplex mode
- » Flow Control

- IEEE802.3x full duplex mode
  - Back-Pressure half duplex mode
  - » VLANs
    - Port-based VLANs
    - IEEE802.1Q Tag VLANs (4096 VID)
    - GVRP (GARP VLAN Registration Protocol)
    - GMRP (GARP Multicast Registration Protocol)
  - » IGMP Snooping
    - IGMP snooping v1/v2/v3
  - » Jumbo Frame
    - Gigabit transmission supports 9K bytes jumbo frame
-

# Specifications

## Technology

### Standards

- IEEE802.3 10BASE-T
- IEEE802.3u 100BASE-TX/100BASE-FX
- IEEE802.3ab 1000BASE-T
- IEEE802.3z 1000BASE-SX/1000BASE-LX
- IEEE802.3x full duplex and flow control

### Forward and Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

### Processing Type

- Store-and-Forward
- Auto Negotiation
- Half duplex back-pressure and IEEE802.3x full-duplex flow control
- Auto-MDI/MDIX

---

## Power

### Input Voltage

- 12VDC

### Power Consumption

- 3W Max. 0.25A @ 12VDC

---

## Mechanical

### Casing

- Metal case
- IP30

### Dimensions

- 100 mm (W) x 122mm (D) x 32.5mm (H)  
(3.94"(W) x 4.8" (D) x 1.28" (H))

### **Weight**

- 350g (0.77lbs.)

### **Installation**

- Wall mounting
- 

## Interface

### **Ethernet Port**

- 10/100/1000BASE-TX: 1 port
- 100/1000BASE SFP slot: 1 port

### **LED Indicators**

- Per Unit: Power Status, OAM loop
  - Per Port: FX/TX Speed, Link/Activity, Full-duplex
- 

## Environment

### **Operating Temperature**

- -5°C to 55°C (-23°F to 131°C)

### **Storage Temperature**

- -20°C to 70°C (-4°F to 158°F)

### **Ambient Relative Humidity**

- 5% to 95% (non-condensing)
- 

## Regulatory Approvals

### **ISO**


- Manufactured in an ISO9001 facility

### **Emission Compliance**

CE Mark Class A

FCC Part 15B Class A

## Dimensions



## Ordering Info

### Model

<b>EL2326-X1Z</b>	10/100/1000BASE-TX to 100/1000BASE-X Dual Rate OAM Managed Media Converter
-------------------	--

### Gigabit Port Options (X)

<b>3</b>	1000BASE-SX (SC) - 550m
<b>4</b>	1000BASE-SX (SC) - 2Km
<b>5</b>	1000BASE-SX (ST) - 550Km
<b>A</b>	1000BASE-LX (SC) - 10Km
<b>B</b>	1000BASE-LX (SC) - 20Km
<b>E</b>	1000BASE-LX (SC) - 40Km (1310nm)
<b>R</b>	1000BASE-BX (SC) WDM – TX: 1310nm/RX: 1550nm-20Km
<b>S</b>	1000BASE-BX (SC) WDM – TX: 1550nm/RX: 1310nm-20Km

### Power Adapter Options (Z)

<b>A</b>	with external power adapter for AU
<b>E</b>	with external power adapter for EU
<b>J</b>	with external power adapter for JP
<b>K</b>	with external power adapter for UK
<b>U</b>	with external power adapter for USA
<b>3C</b>	with external power adapter for China

