

OttoE 08H FE

Hardened 8-port Fast Ethernet Unmanaged Switches



Overview

The **OttoE 08H FE** Series from EtherWAN is a compact, Hardened-grade unmanaged Ethernet switch, built for reliable performance in space-constrained and harsh environments. Designed for simplicity and efficiency, it delivers essential Ethernet networking capabilities at a cost-effective price point.

Supporting a wide input voltage range of **9 to 55VDC** with redundant power options, the OttoE 08H FE also features a relay alarm to signal power failures. The switch offers multiple Fast Ethernet ports, with models available that include both copper and 100Mbps **SFP** ports for extended-distance connections.

With support for auto-negotiation (full/half duplex) and auto MDI/MDIX, device connection is straightforward and hassle-free. **QoS** (Quality of Service) functionality ensures traffic prioritization for optimized network performance. Housed in a rugged metal enclosure designed for DIN rail mounting, the OttoE 08H FE is built for easy installation and long-term durability—mounting kit included.

Deployment scenarios: Automation, Railway, Intelligent Intersection

EtherWAN — "When Connectivity is Crucial."

Highlight

+ Reliable Operation

- Redundant dual power input 12/24/48 VDC

+ SFP Connectivity

- Up to two 100BASE SFP option

+ Rugged Design

- Fanless design (No moving parts)
- Wide temperature -40 to 75°C

+ QoS Prioritized Messages

- EtherNet/IP (UDP 2222)

Specifications

+ Interface

Ethernet

- 10/100BASE-TX: 6/8-ports
- 100BASE-SFP: 0/2-ports

Alarm Contact

- One relay output with current 0.5A@30V

LED Indicators

- Per Unit: Power 1 (Green), Power 2 (Green), Fault (Red)
- Per Port: Link/Activity (Green)

+ Physical

Casing Material

- Metal

IP Rating

- IP30

Dimensions

- 45 x 75 x 100mm (W x D x H) (1.77" x 2.95" x 3.94")

Weight

- 336g (0.74lbs)

Installation Type

- DIN-Rail (Top hat type 35mm) mounting

+ Technology

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.1p Quality of Service (QoS)

Forward/Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps

Packet Buffer Memory

- 768K bits

Processing Type

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure
- Auto MDI/MDIX

Address Table Size

- 2K MAC

+ Regulatory

ISO

- Manufactured in ISO-9001 facility

EMI

- FCC Part 15 Class A
- VCCI Class A
- EN 61000-6-4
- ICES-003
- EN 55032
- BSMI

EMS

- EN 61000-6-2
 - - EN 61000-4-2 (ESD)
 - - EN 61000-4-3 (Radiated RFI)
 - - EN 61000-4-4 (Burst)
 - - EN 61000-4-5 (Surge)
 - - EN 61000-4-6 (Induced RFI)
 - - EN 61000-4-8 (Magnetic field)

Safety

- UL 61010

Environmental Test Compliance

- IEC 60068-2-6 Fc (Vibration)
- IEC 60068-2-27 Ea (Shock)
- FED STD 101C Method 5007.1
- (Free fall w/package)

Industrial

- EN 50121-4

+ Power

Input

- 9-55VDC (Terminal Block)

Power Consumption

- 3.4W max.

Protection

- Reverse Polarity Protection

+ Warranty

Length

- Limited Lifetime

Details

- www.etherwan.com/support/warranty-policy

+ Environmental

Operating Temp.

- -40 to 75°C (40 to 167°F)

Storage Temp.

- -40 to 85°C (-40 to 185°F)

Relative Humidity

- 5% to 95% (non-condensing)

+ What's Included

Device


- Ethernet switch

Dimensions

Hardened grade unmanaged 8 ports Ethernet switch

Image not found or type unknown

Application



Ordering Info

+ Fast Ethernet models

+ Gigabit Ethernet models

	 TF100H-0800	 TF100H-0602	 TF100H-0800
10/100BASE TX	8	6	8
100BASE SFP	-	2	-
Power Input	2 (9~55VDC) Push-in spring terminal block		2 (9~55VDC) termin
QoS	EtherNet/IP		Ether
Corrosion Resistant	IP30		IP
	Quote	Quote	Quote

+ Optional Accessories

HDR-30-24	30W/1.5A DIN-Rail 24VDC Hardened Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Hardened Power Supply

100BASE SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver
---------------------	--

