

OttoE 16 GE

Industrial 16-port Gigabit Ethernet Unmanaged Switches



Overview

EtherWAN **OttoE 16 GE** Series – Industrial Grade Unmanaged Ethernet Switch

The OttoE 16 GE Series from EtherWAN is a robust, unmanaged Ethernet switching solution engineered for reliable operation in space-constrained and demanding industrial environments. Designed for simplicity and cost-efficiency, it delivers core networking functionality essential for industrial applications.

The switch supports a wide input voltage range of **10 to 55VDC** with redundant power capability and includes a relay alarm to signal power failure events, enhancing system reliability.

Featuring auto-negotiation (full/half duplex) and auto MDI/MDIX, the OttoE 16 GE ensures seamless integration with diverse network devices. Built-in **QoS** (Quality of Service) enhances traffic management by enabling prioritization of critical data. The unit is housed in a rugged metal enclosure, DIN rail mountable for secure and straightforward installation—mounting kit included.

Deployment scenarios: Automation, Railway, Intelligent Intersection

EtherWAN — "**When Connectivity is Crucial.**"

Highlight

+ Reliable Operation

- IEEE 802.3az Energy Efficient Ethernet
- Power failure notification

+ Corrosion Resistant

- IP30 design

+ Rugged Design

- Fanless design (No moving parts)
- Reverse Polarity Protection

+ QoS Prioritized Messages

- EtherNet/IP (UDP 2222)
- PROFINET (Ethertype 0x8892)

Specifications

+ Interface

Ethernet

- 10/100/1000BASE-TX: 16-ports

Alarm Contact

- One relay output with current 0.5A@48V

LED Indicators

- Per Unit: Power 1 (Green), Power 2 (Green), Fault (Red)
- Per Port: Link/Activity (Green)
- Per Port: Speed (Yellow)

+ Physical

Casing Material

- Metal

IP Rating

- IP30

Dimensions

- 80 x 91 x 100mm (W x D x H) (3.15" x 3.58" x 3.94")

Weight

- 502g (1.11lbs)

Installation Type

- DIN-Rail (Top hat type 35mm) mounting

+ Technology

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.1p Quality of Service (QoS)

Forward/Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

Packet Buffer Memory

- 2M bits

Processing Type

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure
- Auto MDI/MDIX

Address Table Size

- 8K MAC

+ Regulatory

ISO

- Manufactured in ISO-9001 facility

EMI

- FCC Part 15 Class A
- VCCI Class A
- EN 61000-6-4
- ICES-003
- EN 55032
- BSMI

EMS

- EN 61000-6-2
 - - EN 61000-4-2 (ESD)
 - - EN 61000-4-3 (Radiated RFI)
 - - EN 61000-4-4 (Burst)
 - - EN 61000-4-5 (Surge)
 - - EN 61000-4-6 (Induced RFI)
 - - EN 61000-4-8 (Magnetic field)

Safety

- UL 61010

Environmental Test Compliance

- IEC 60068-2-6 Fc (Vibration)
- IEC 60068-2-27 Ea (Shock)
- IEC 60068-2-31
- (Free fall w/package)

Industrial

- EN 50121-4

+ Power

Input

- 10-55VDC (Terminal Block)

Power Consumption

- TBD

Protection

- Reverse Polarity Protection

+ Warranty

Length

- Limited Lifetime

Details

- www.etherwan.com/support/warranty-policy

+ Environmental

Operating Temp.

- -10 to 60°C (14 to 140°F)

Storage Temp.

- -40 to 85°C (-40 to 185°F)

Relative Humidity


- 5% to 95% (non-condensing)

+ What's Included


Device

- Ethernet switch

Dimensions



Application



Ordering Info

+ Fast Ethernet models



TG100-1600

10/100Base TX	16
100Base SFP	-
Power Input	2 (10 - 55VDC) Push-in spring terminal block
QoS	EtherNet/IP, Profinet
Corrosion Resistant	IP30

[Quote](#)

+ Optional Accessories

HDR-30-24	30W/1.5A DIN-Rail 24VDC Hardened Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Hardened Power Supply

