

EX73900E Series

Hardened Managed 10 to 16-Port Gigabit Ethernet Switch



Overview

EtherWAN's EX73900E series is a hardened DIN-rail mounted managed Ethernet switch platform. Equipped with up to 12 gigabit Ethernet and 4 dual-rate gigabit SFP ports, and the IEEE1588v2 Precision Time Protocol (PTP) that uses network packets and time stamps for network time synchronization. The EX73900E series provides flexibility, speed, and reliability to support networks for urban infrastructure, transportation, security, power substations, and other areas where connectivity is crucial.

EtherWAN — "When Connectivity is Crucial."

Highlights

+ High Bandwidth and Versatility

8 or 12 10/100/1000BASE-T(X) ports for High bandwidth connections
Up to 4 Dual-rate 100/1000BASE SFP uplink ports for fiber connections
Full capacity switching running at full duplex

+ Hardened-Grade for Non-Ventilated & Harsh Environments

Wide operating temperature range -40 to 75°C (-40 to 167°F)
Fanless operation
High impact, thermal shock, and electrical noise resistance

+ Lite Layer 3 Functionality

Static routing, RIP v1/v2, and OSPF support
Redundancy with VRRP
Reduces amount of broadcast traffic

+ Compliance

IEC 61850-3/IEEE 1613 certified for power substations
NEMA TS2 rated
UL certified for safety

+ Management/Security Features

Port control
Dying gasp feature provides SNMP trap upon power off
Configure and monitor with eVue™ and eLite™

+ Support

Complimentary Technical Support
Free Firmware Upgrades
Limited Lifetime Warranty

Features

+ Interface

CLI, Telnet, Web GUI

+ Management

Firmware upgrade
Configuration backup
DHCP Server/Client
RMON (Remote Monitoring)
Port Mirroring
NTP (Network Time Protocol) synchronization
LLDP (Link Layer Discovery Protocol)
IPv4/IPv6
SNMP v1/v2c/v3
Modbus TCP

+ Security

MAC Address filtering
Enable/Disable port
Storm control
System logging
IEEE 802.1x LAN Access control

Remote authentication through RADIUS and TACACS+
 Complex password support
 Multi-user login and privileged access management
 SSH for CLI and Telnet security
 SSL and HTTPS for web security
 ACL (Access Control List, up to 4096 entries)

+ Quality of Service (QoS)

Priority Queues: 8 queues per port
 Traffic classification based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin), and strict mode
 Rate Limiting (Ingress/Egress)

Specifications

+ Interface

Ethernet
 8 or 12 x 10/100/1000BASE-T(X)
 2 or 4 x 100/1000BASE SFP

Console
 1 x RJ45

Config Backup
 1 x USB (Type A Connector)

Digital Input
 2 x Digital Input
 Wet Contact: 0-3V for State 0; 13-30V for State 1;
 Max Input Current: 8mA
 Dry Contact: Logic Level 1–Close to GND; Logic Level 0–Open

Alarm Contact
 2 x Relay output, current capacity 0.6A/30VDC

LED Indicators
 Per Unit: Power 1, Power 2, Alarm
 Per Port: Link/Activity

+ Technology

Standards
 IEEE 802.3 10BASE-T
 IEEE 802.3u 100BASE-TX/100BASE-FX
 IEEE 802.3ab 1000BASE-T
 IEEE 802.3ad link aggregation control
 IEEE 802.3z 1000BASE-SX/1000BASE-LX
 IEEE 802.3x full duplex and flow control

+ Layer 2 Features

Auto-negotiation for port speed and duplex
 Flow Control
 IEEE 802.3x full duplex mode
 Back-pressure half duplex mode

Redundant Protocols
 IEEE 802.1D STP
 IEEE 802.1w RSTP
 IEEE 802.1s MSTP
 EtherWAN's Alpha-Ring network fault recovery

VLANs
 IEEE 802.1Q Tag VLANs
 GVRP
 GMRP

Link Aggregation
 Static Trunk (4 groups)
 IEEE 802.3ad LACP

IGMP Snooping v1/v2/v3

+ Layer 3 Features

IP Packet Routing
 Maximum number of routes in hardware: 64 entries
 Static Routing
 RIP v1/v2
 OSPF v2

Routing Redundancy
 VRRP

+ Software Properties and Performance

Switching Fabric
 32Gbps

Forwarding Rate
 23.5Mpps

Total VLAN Entries
 256 (4096 VID)

Jumbo Frame Size
 9KB

MAC Table Size
 16K

Packet Buffer Memory
 12M bits

IEEE 802.1D STP
IEEE 802.1p QoS
IEEE 802.1Q Tag VLANs
IEEE 802.1s MSTP
IEEE 802.1w RSTP
IEEE 802.1x PNAC
IEEE 802.1ab LLDP
IEEE 1588v2 PTP

Forward/Filtering Rate
14,880pps for 10Mbps
148,810pps for 100Mbps
1,488,100pps for 1000Mbps

Processing Type
Store-and-forward
Auto-negotiation
Half-duplex back-pressure and full-duplex flow control
Auto MDI/MDIX

System Memory
2Gb DDR3 SDRAM

Flash Storage
1Gb

+ Power

Input
12-48VDC Redundant (Terminal block)

Power Consumption
20W Max

Protection
Reverse Polarity Protection
Overload Current Protection

+ Physical

Casing Material
Aluminum

IP Rating
IP40

Dimensions
72 x 140 x 170mm (W x D x H)
2.8" x 5.5" x 6.7"

Weight
1.4kg (3.08lbs)

Installation Type
DIN-rail mounting

+ Environmental

Operating Temp.
-40 to 75°C (-40 to 167°F)

Storage Temp.
-45 to 85°C (-49 to 185°F)

Relative Humidity
5% to 95% (non-condensing)

+ Regulatory

ISO
Manufactured in ISO-9001 facility

EMI
FCC Part 15B Class A
VCCI Class A
EN 61000-6-4
EN 61000-3-2
EN 61000-3-3

EMS
EN 61000-6-2
EN 61000-4-2 (ESD)
EN 61000-4-3 (Radiated RFI)
EN 61000-4-4 (Burst)
EN 61000-4-5 (Surge)
EN 61000-4-6 (Induced RFI)
EN 61000-4-8 (Magnetic field)

Safety
UL 61010

Traffic
NEMA TS2

Rail
EN 50121-4

Power Substation
IEC 61850-3/IEEE 1613

Vibration
IEC 60068-2-6

Shock
IEC 60068-2-27

Free Fall
FED STD 101C Method 5007.1

+ Warranty

Length
Limited Lifetime

Details
www.etherwan.com/support/warranty-policy

+ What's Included

Device

Ethernet Switch

Cables

1 Console Cable


Installation

Mounting brackets, screws


Documentation

Quick install guide

Dimensions




Application




Software

Network Management [eVue™ Network Configuration and Monitoring Tool](#)
 Network Discovery [eLite™ Network Discovery and IP Configuration Tool](#)



IP	System Name	Group
192.168.50.12	EG99-5012	
192.168.50.62	EX709-5062	
192.168.50.254	R50	
192.168.50.11	EG99-5011	
192.168.50.63	EX74-5063	
192.168.50.14	EX779-5014	
192.168.50.61	EX71v2-5061	
192.168.50.44	EX71-5044	
192.168.50.64	EX73-5064	
192.168.50.34	EX739-5034	

Acknowledged	ID	Severity	Time	Service	Node	Message
✓	5107	Normal	6/28/2019, 9:50:35 AM	login	server	User 'admin' logged in.
✓	5106	Normal	6/27/2019, 10:00:50 AM	login	server	User 'admin' logged in.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Web 192.168.1.19 is down.
✓	5105	Major	6/24/2019, 1:18:23 PM	ping-monitor	192.168.1.19	Teinet 192.168.1.19 is down.
✓	5104	Normal	6/24/2019, 1:12:34 PM	login	server	User 'admin' logged in.



IP Address	MAC Address
192.168.50.22	00:e0:b3:50:22:00
192.168.50.31	00:e0:b3:50:31:00
192.168.50.72	00:e0:b3:50:72:00
192.168.50.55	00:e0:b3:50:55:00
192.168.50.23	00:e0:b3:50:23:00
192.168.50.73	00:e0:b3:50:73:00
192.168.50.44	00:e0:b3:50:44:00
192.168.50.64	00:e0:b3:50:64:00
192.168.50.43	00:e0:b3:50:43:00
192.168.50.62	00:e0:b3:50:62:00
192.168.50.71	00:e0:b3:50:71:00
192.168.50.24	00:e0:b3:50:24:00

Ordering Info

+ Model

- EX73934E-0VB 12-port 10/100/1000BASE-T(X) + 4-port 100/1000BASE SFP
- EX73924E-0VB 8-port 10/100/1000BASE-T(X) + 4-port 100/1000BASE SFP
- EX73922E-0VB 8-port 10/100/1000BASE-T(X) + 2-port 100/1000BASE SFP

+ Accessories

- Hardened 100BASE SFP Modules www.etherwan.com/products/sfp-fiber-transceiver
- Hardened Gigabit SFP Modules www.etherwan.com/products/sfp-fiber-transceiver
- DIN-Rail Power Supplies www.etherwan.com/products/din-rail-power-supply
(*)
- *Recommended Power Supply EX41-145046 Power Supply 45W 12VDC with Open Wire

