

OttoE 08 GE

工業級非網管型 8 埠 Gigabit 乙太網路交換器



產品介紹

EtherWAN 益網科技 **OttoE 08 GE** 系列是一款極緻型工業級非管理式乙太網交換機，專為空間受限與嚴苛環境中的穩定運作而設計。此系列產品以簡潔高效為核心理念，提供基本乙太網功能，並具備極高的性價比。

OttoE 08 GE 支援 **9 到 55VDC** 的寬電壓輸入範圍，並具備冗餘電源選項與繼電器警報功能，可在電源異常時即時發出警示。該交換機提供多個 Gigabit 乙太網埠，型號涵蓋銅纜埠與 100/1000Mbps 雙速率 SFP 光纖埠，適用於長距離連接需求。

支援自動協商（全雙工/半雙工）與自動 MDI/MDIX 功能，讓設備連接更為直覺簡便。內建**QoS (服務品質)** 功能可有效優化網路流量優先順序，提升整體網路效能。OttoE 08 GE 採用堅固金屬外殼，支援導軌安裝，安裝簡便且耐用，並隨附安裝配件。

適用場域：

- ◆ 工業自動化系統
- ◆ 鐵路與交通控制
- ◆ 智慧路口與監控系統
- ◆ 公共建設

益網科技 - “ 連結，制勝的關鍵 ”

產品亮點

+ 可靠的運作機制

- 雙電源輸入12/24/48 VDC

+ SFP 連接埠

- 最多可支援達兩個 100/1000BASE SFP

+ 高可靠性

- 無風扇設計

+ QoS 封包排程

- EtherNet/IP (UDP 2222)
- PROFINET (Ether type 0x8892)

產品規格

+ Interface

Ethernet

- 10/100/1000BASE-TX: 6/8-ports
- 100/1000BASE-SFP: 0/2-ports

Alarm Contact

- One relay output with current 0.5A@30V

LED Indicators

- Per Unit: Power 1 (Green), Power 2 (Green), Fault (Red)
- Per Port: Link/Activity (Green)

+ Physical

Casing Material

- Metal

IP Rating

- IP30

Dimensions

- 45 x 75 x 100mm (W x D x H) (1.77" x 2.95" x 3.94")

Weight

- 336g (0.74lbs)

Installation Type

- DIN-Rail (Top hat type 35mm) mounting

+ Technology

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.1p Quality of Service (QoS)
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-SX/1000BASE-LX

Forward/Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

Packet Buffer Memory

- 1.5M bits

Processing Type

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure
- Auto MDI/MDIX

Address Table Size

- 4K MAC

+ Regulatory

ISO

- Manufactured in ISO-9001 facility

EMI

- FCC Part 15 Class A
- VCCI Class A
- EN 61000-6-4
- ICES-003
- EN 55032
- BSMI

EMS

- EN 61000-6-2
 - - EN 61000-4-2 (ESD)
 - - EN 61000-4-3 (Radiated RFI)
 - - EN 61000-4-4 (Burst)
 - - EN 61000-4-5 (Surge)
 - - EN 61000-4-6 (Induced RFI)
 - - EN 61000-4-8 (Magnetic field)

Safety

- UL 61010

Environmental Test Compliance

- IEC 60068-2-6 Fc (Vibration)
- IEC 60068-2-27 Ea (Shock)
- FED STD 101C Method 5007.1
- (Free fall w/package)

Industrial

- EN 50121-4

+ Power

Input

- 9-55VDC (Terminal Block)

Power Consumption

- 3.4W max.

Protection

- Reverse Polarity Protection

+ Warranty

Length

- Limited Lifetime

Details

- www.etherwan.com/support/warranty-policy

+ Environmental

Operating Temp.

- -10 to 60°C (14 to 140°F)

Storage Temp.

- -40 to 85°C (-40 to 185°F)

Relative Humidity


- 5% to 95% (non-condensing)


+ What's Included

Device


- Ethernet switch

產品尺寸





產品應用



訂購資訊

+ Fast Ethernet models



TG100-0800



TG100-0602

10/100/1000BASE TX	8	6
100/1000BASE SFP	-	2
Power Input	2 (9~55VDC) Push-in spring terminal block	
QoS	EtherNet/IP	
Corrosion Resistant	IP40	
	Quote	Quote

+ Optional Accessories

HDR-30-24	30W/1.5A DIN-Rail 24VDC Hardened Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Hardened Power Supply
100BASE SFP Modules	www.etherwan.com/products/sfp-fiber-transceiver

