

EX78162 系列

強固級網管型 16埠10/100BASE PoE + 2埠Gigabit 乙太網路交換器



產品介紹

本產品自2020年5月15日起停產。請點選 [此處](#) 尋找替代產品。

EX78162系列強固乙太網路交換器，採鋁軌式安裝，提供16個10/100BASE PoE連接埠及兩個Gigabit LC光纖埠。IEEE 802.3at PoE網路埠，每埠最高可支援30W，總供電瓦數為240W，可廣泛應用於許多終端受電(PD)設備，例如PTZ 球型攝影機、無線基地台及軌旁通訊設備等。

透過益網獨家技術Alpha-Ring環狀網路備援機制，可在網路斷線時迅速啟動備援機制，於15毫秒內恢復連線通訊。

EX78162系列具備完整管理功能，包含port security, IGMP snooping, port-based VLAN, GARP 協定, link aggregation；使用者可透過網頁瀏覽, telnet, SSH, SNMP, RMON, TFTP,和RS-232 console 管理介面，執行各種等級的網路管理。

EX78162系列專為嚴峻戶外環境設計打造，工業等級設計，可承受強力的落摔衝擊、防震動及抗電磁波干擾，更可在 -40 到 75°C 寬溫環境下穩定運作。

EtherWAN — "When Connectivity is Crucial."

產品亮點

PoE連接埠

- » 1-16埠支援IEEE 802.3at /af PoE供電標準

強固等級設計

- » 寬溫操作(-40 到75°C)
- » 無風扇和堅固的金屬外殼設計，可有效避免高溫及高濕度環境導致材質老化
- » 抗震動及抗電磁波干擾

智慧化管理功能

- » 完整的網路管理效能：QoS, VLAN,ACL和支援RADIUS

產品特色

Management

- » Interface
 - CLI, Telnet and Web Browser
 - SNMP v1/v2c/v3
 - » Firmware and configuration upgrade and backup via TFTP
 - » Supports DHCP Server/Client
 - » RMON (Remote monitoring): group 1, 2, 3, 9
 - » Port mirroring: TX/RX and both
 - » SFP transceivers support Digital Diagnostics Monitoring (DDM)
 - » NTP (Network Time Protocol) time synchronization
 - » IEEE 802.1ab LLDP (Link Layer Discovery Protocol)
-

Security

- » MAC address filtering
 - » Enable/disable port
 - » Storm control (broadcast and multicast types)
 - » IEEE 802.1x LAN access control
 - » Remote authentication through RADIUS
 - » SSH for CLI and Telnet security
 - » SSL for web security
 - » Multi-level user account/password against unauthorized configuration
 - » System log (remote/local)
-

Quality of Service (QoS)

- » Priority Queues: 4 queues per port
 - » Traffic classification based on IEEE 802.1p CoS, DSCP, WRR (Weighted round robin) and strict mode
 - » Rate Limiting (Ingress/Egress)
-

Layer 2 Features

- » Auto-negotiation for port speed and duplex mode
- » Flow Control
 - IEEE 802.3x full duplex mode

- Back-Pressure half duplex mode
- » Redundant Protocol
 - IEEE 802.1D Spanning Tree Protocol (STP)
 - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
 - EtherWAN's Alpha-Ring network fault recovery (<15ms)
- » VLANs
 - Port-based VLANs
 - IEEE 802.1Q Tag VLANs (128 groups, 4096 VID)
 - GVRP (GARP VLAN Registration Protocol)
 - GMRP (GARP Multicast Registration Protocol)
- » Link Aggregation
 - Static Trunk (2 groups, support MAC base)
 - IEEE 802.3ad Link Aggregation Control Protocol
- » IGMP Snooping
 - IGMP snooping v1/v2/v3
- » Performance
 - Switching Capability: 7.2Gbps
 - Packet Buffer Size: 2M
 - MAC Address Table: 8K

產品規格

技術

標準

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/100BASE-FX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-SX/1000BASE-LX
- IEEE 802.3x Full duplex and flow control
- IEEE 802.1p QoS
- IEEE 802.1Q Tag VLANs
- IEEE 802.1w RSTP
- IEEE 802.1x Port-based Network Access Control
- IEEE 802.3af/at Power over Ethernet (PoE)

Forward and Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

緩衝記憶體封包

- 2M bits

傳輸型式

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure and IEEE 802.3x full-duplex flow control
- Auto MDI/MDIX

MAC地址表

- 8192 MAC addresses
-

電源

輸入電壓

- Redundant power inputs
Terminal Block: 52–57VDC

電力功耗

- Device: Max. 15W (without PoE)
- PoE Power Budget (depends on power input): 240W Max.

PoE Technology

- Alternative B
Pins 7/8(-), 4/5(+)

PoE Power Output

- Port 1 to 16 support PoE
- IEEE 802.3af: up to 15.4W/port, 47-57VDC
- IEEE 802.3at: up to 30W/port, 52-57VDC

Protection

- Reverse polarity protection
-

機構

機殼

- 金屬材質
- IP30

尺寸

- 71.4 x 140 x 170mm (W x D x H)
(2.85" x 5.6" x 6.8")

重量

- 1.44 Kg (3.17lbs.)

安裝方式

- DIN-Rail
-

介面

乙太網路埠

- 10/100BASE-TX (PoE): 16 ports
- Gigabit SFP: 2 ports

Console Port

- Port: One DB9 RS-232 port

Alarm Contact

- One relay output with current 1A/250VAC

LED 指示燈號

- Per Unit: Power
 - Per Port: Link/Activity (Green)
 - Per PoE Port: PoE (Orange)
-

環境

工作溫度

- -40 to 75°C (-40 to 167°F)
Tested @ -40 to 85°C (-40 to 185°F)

儲存溫度

- -45 to 85°C (-49 to 185°F)

工作濕度

- 5% to 95% (無凝結)
-

通過認證

ISO

- Manufactured in an ISO 9001 facility

EMI

FCC Part 15B Class A

EN 61000-3-2

EN 61000-3-3

EN 61000-6-4

EMS

EN 61000-6-2

- EN 61000-4-2 (ESD Standards)
- EN 61000-4-3 (Radiated RFI Standards)
- EN 61000-4-4 (Burst Standards)
- EN 61000-4-5 (Surge Standards)
- EN 61000-4-6 (Induced RFI Standards)
- EN 61000-4-8 (Magnetic Field Standards)


Environmental Test Compliance

IEC 60068-2-6 Fc (Vibration)

IEC 60068-2-27 Ea (Shock)

IEC 60068-2-32 Ed (Free fall)

產品尺寸圖



訂購型號

型號

EX78162-0VB	16-port 10/100BASE-TX PoE +2-port Gigabit SFP Hardened Managed Ethernet Switch
--------------------	--

* DIN-Rail mounting kit included.

Optional Accessories

SDR-480-48	480W/10A DIN-Rail 48VDC Industrial Power Supply
-------------------	---



© EtherWAN Systems, Inc. All rights reserved. 20230309

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.