

EX19082

Smart Managed 10-Port Gigabit PoE Ethernet Switch



Overview

EtherWAN's EX19082 is a 10-port Gigabit Power over Ethernet switch with high performance and features suited for small-business and commercial environments. The EX19082 is equipped with 8 10/100/1000BASE-T(X) PoE+ ports and 2 Gigabit uplink ports (1 TX + 1 SFP). With features such as an easy-to-use management GUI, QoS, VLANs and full wire speed throughput, port speeds up to gigabit for 4K cameras and higher, and a power budget of 240W, the EX19082 is the perfect solution for security networks.

EtherWAN — "When Connectivity is Crucial."

Highlights

+ Smart Management Features

- Easy to use web GUI
- VLAN configuration
- Comprehensive IP configuration and QoS

+ Power over Ethernet

- Total PoE power budget of 240W to deliver sufficient power to all connected PoE devices
- Overloading protection
- Power and data over a single cable with gigabit speed capable of handling cameras with 4K resolution and higher and other high bandwidth devices

Software Features

+ Interface

Web GUI

+ Management

Firmware upgrade

Configuration backup and restore

DHCP Client

SNMP Trap

Port Mirroring

LLDP (Link Layer Discovery Protocol)

+ Security

MAC address filtering

Enable/Disable PoE per port

Storm control

TCP/UDP filter

Initial login complex password setup requirement

+ Quality of Service (QoS)

Priority Queues: 8 queues per port

Traffic classification based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin)

+ Layer 2 Features

Auto-negotiation for port speed and duplex mode

Flow Control

IEEE 802.3x full duplex mode

Back-pressure half duplex mode

VLANs

16 Groups, 4096 VID

Tag-based

Port-based

Link Aggregation

Static Trunk (2 groups)

IGMP Snooping

IGMP Snooping v1/v2

+ Software Properties and Performance

Switching Fabric

20Gbps

Forwarding Rate

14.88Mpps

Jumbo Frame Size

9.6KB

MAC Table Size

8K

Packet Buffer Memory

4Mb

Hardware Specifications

+ Interface

Ethernet

- 10/100/1000BASE-T(X): 8 PoE+ ports + 1 TX port
- 100/1000BASE SFP: 1 port

LED Indicators

- Per Unit: Power
- Per Port PoE: Status
- Per Port Link: Link/Activity

Reset Button

- Restore factory default settings

+ Technology

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-SX/1000BASE-LX
- IEEE 802.3x Full duplex and flow control
- IEEE 802.1p QoS
- IEEE 802.1Q Tag VLANs
- IEEE 802.3af Power over Ethernet (PoE)
- IEEE 802.3at Power over Ethernet (PoE+)
- IEEE 802.1AB LLDP (Link Layer Discovery Protocol)
- IEEE 802.3az EEE (Energy Efficient Ethernet)

Forward and Filtering Rate

- 14,880pps for 10Mbps
- 148,880pps for 100Mbps
- 1,488,000pps for 1000Mbps

Processing Type

- Store-and-Forward
- Auto-Negotiation
- Half-duplex back-pressure full-duplex flow control
- Auto MDI/MDIX

+ Power

Input

- 100-240VAC, 50/60Hz

Power Consumption

- Device: 23W (without PoE)
- PoE Power Budget: 240W

+ Physical

Casing Material

- Metal

Dimensions

- 266 x 161 x 44mm (W x D x H)
- 10.5" x 6.34" x 1.73"

Weight

- 4lbs (1.8kg)

Installation Type

- Rack mounting, Desktop

+ Environmental

Operating Temp.

- 0 to 50°C (32 to 122°F)

Storage Temp.

- -10 to 70°C (14 to 158°F)

Relative Humidity

- 10% to 90% (non-condensing)

+ Regulatory

ISO

- Manufactured in ISO-9001 facility

EMI

- FCC Part 15 Class B

Safety

- UL 60950-1

+ Warranty

Length

- 3 Years

Details

- www.etherwan.com/support/warrantypolicy

+ What's Included

Device

- Ethernet Switch

Power

- AC power cord


Installation

- Mounting brackets, screws

Documentation

- Quick Install Guide

Dimensions



Ordering Info

+ Model

EX19082	8-port 10/100/1000BASE-T(X) PoE + 1-port 10/100/1000BASE-T(X) + 1-port 100/1000BASE SFP
---------	---

