

### **EX19082A** Unmanaged 10-Port Gigabit PoE Ethernet Switch





## **Overview**

EtherWAN's EX19082A is a 10-port Gigabit Power over Ethernet switch with high performance and features suited for small-business and commercial environments. The EX19082A is equipped with 8 10/100/1000BASE-T(X) PoE+ ports and 2 Gigabit uplink ports (1 TX + 1 SFP). With full wire speed throughput, port speeds up to gigabit for 4K cameras and higher, and a power budget of 240W, the EX19082A is the perfect solution for security networks.

EtherWAN — "When Connectivity is Crucial."

# Highlights

#### + Power over Ethernet

Total PoE power budget of 240W to deliver sufficient power to all connected PoE devices Overloading protection

Power and data over a single cable with gigabit speed capable of handling cameras with 4K resolution and higher and other high bandwidth devices



# **Hardware Specifications**

#### + Interface

**Ethernet** 10/100/1000BASE-T(X): 8 PoE+ ports + 1 TX port 1000BASE SFP: 1 port

LED Indicators Per Unit: Power Per Port PoE: Status Per Port Link: Link/Activity

### + Technology

#### Standards

IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-SX/1000BASE-LX IEEE 802.3x Full duplex and flow control IEEE 802.3af Power over Ethernet (PoE) IEEE 802.3at Power over Ethernet (PoE+)

#### **Forward and Filtering Rate** 14,880pps for 10Mbps

148,880pps for 100Mbps 1,488,000pps for 1000Mbps

#### **Processing Type**

Store-and-Forward Auto-Negotiation Half-duplex back-pressure full-duplex flow control Auto MDI/MDIX

Switching Fabric 20Gbps

MAC Table Size 8K

Packet Buffer Memory 4Mb

#### + Power

Input 100-240VAC, 50/60Hz

Power Consumption Device: 23W (without PoE) PoE Power Budget: 240W

### + Physical

**Casing Material** Metal

Dimensions 266 x 161 x 44mm (W x D x H) 10.5" x 6.34" x 1.73"

Weight 4lbs (1.8kg)

Installation Type Rack mounting, Desktop



### + Environmental

**Operating Temp.** 0 to 50°C (32 to 122°F)

**Storage Temp.** -10 to 70°C (14 to 158°F)

Relative Humidity 10% to 90% (non-condensing)

### + Regulatory

**ISO** Manufactured in ISO-9001 facility

**EMI** FCC Part 15 Class B

**Safety** UL 60950-1

## **Dimensions**

### + Warranty

Length 3 Years

Details www.etherwan.com/support/warrantypolicy

### + What's Included

**Device** Ethernet Switch

**Power** AC power cord

**Documentation** Quick Install Guide





# **Ordering Info**

### + Model

EX19082A 8-port 10/100/1000BASE-T(X) PoE + 1-port 10/100/1000BASE-T(X) + 1-port 1000BASE SFP



© EtherWAN Systems, Inc. All rights reserved. 20240919

EtherWAN is constantly developing and improving products. Specifications are subject to change without notice and without incurring any obligation.