

EX41941

Hardened Unmanaged 4-Port Gigabit PoE & 1-Port Gigabit RJ45 Ethernet Switch

image not found or type unknown



Overview

EtherWAN's EX41941 is a compact hardened unmanaged PoE switch which can be wall or DIN-rail mounted. 4 gigabit PoE ports provide up to 30W output per port with a PoE power budget of 120W, ensuring that the maximum possible power is delivered to every device at all times. 1 RJ45 uplink port provides flexibility for data transmission and cascading. The EX41941 provides the power required to support various security and other network applications, along with flexibility, speed, and reliability to support networks.

EtherWAN — "When Connectivity is Crucial."

Highlights

+ High-Power PoE (Power over Ethernet)

- Up to 30W output per port for various security, LED lighting, and other applications
- Total PoE power budget of 120W
- Backward compatible with 802.3af devices

+ Hardened-Grade for Non-Ventilated & Harsh Environments

- Wide operating temperature range -40 to 75°C (-40 to 167°F)
- Fanless operation
- High impact, thermal shock, and electrical noise resistance

+ Support

- Complimentary Technical Support
- In-person training and free online training courses available
- Limited Lifetime Warranty

Specifications

+ Interface

Ethernet

- 5 x 10/100/1000BASE-T(X)

LED Indicators

- Per Unit: Power 1, Power 2
- Per Port: Link/Activity

+ Technology

Standards

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/100BASE-FX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3x full duplex and flow control
- IEEE 802.3af PoE
- IEEE 802.3at PoE+

Forward/Filtering Rate

- 14,800pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

Processing Type

- Store-and-forward
- Auto-negotiation
- Half-duplex back-pressure and full-duplex flow control
- Auto MDI/MDIX

+ Switch Properties and Performance

Switching Fabric

- 10Gbps

Jumbo Frame Size

- 9KB

MAC Table Size

- 2K

Packet Buffer Memory

+ Power

Input

- 48-56VDC Redundant (Terminal block)+ 48-56VDC Power DIN Connector

Power Consumption

- 2.24W max @ 48VDC, without PoE

PoE Power Output

- Per Port: Up to 30W/port
- Power Budget: 120W

Protection

- Reverse Polarity Protection
- Current Overload Protection

+ Physical

Casing Material

- Aluminum

IP Rating

- IP30

Dimensions

- 1.26" x 3.21" x 4.07" (W x D x H)
32 x 81.5 x 103.5mm

Weight

- 1.0lbs (0.45kg)

Installation Type

- DIN-rail or wall/panel mounting

+ Environmental

Operating Temp.

- -40 to 167°F (-40 to 75°C)

Storage Temp.

- -49 to 185°F (-40 to 85°C)

Relative Humidity

- 5% to 95% (non-condensing)

+ Regulatory

ISO

- Manufactured in ISO-9001 facility

EMI

- FCC Part 15B Class A
- EN 55032
- EN 55024

EMS

- EN 61000-4-2 (ESD)
- EN 61000-4-4 (Burst)
- EN 61000-4-5 (Surge)

Safety

- UL 60950-1

Vibration

- IEC 60068-2-6

Shock

- IEC 60068-2-27

Free Fall

- EN 60068-2-32

+ Warranty

Length

- Limited Lifetime

Details

- www.etherwan.com/support/warranty-policy

+ What's Included

Device

- Switch

Installation

- Mounting brackets, screws, 4-pin terminal block

Documentation

- Quick install guide

Dimensions

EX41941 Dimensions
Image not found or type unknown

Ordering Info

+ Model

EX41941 4-port 10/100/1000BASE-T PoE + 1-port Gigabit RJ45 Ethernet Switch

+ Accessories

Power Supplies www.etherwan.com/products/power-supplies

