

# ED3575

Hardened Managed 6-port 10/100BASE-TX +2-port Gigabit combo SFP Switch with 2-port Copper Pair Extender



## Overview

EtherWAN's ED3575 is a hardened managed Ethernet switch and extender combo. Equipped with Ethernet, SFP, and copper extender ports, the ED3575 bridges the gap between modern and legacy infrastructures, providing the flexibility and versatility for networks in urban infrastructure, transportation, security, and other areas where connectivity is crucial.

EtherWAN — "When Connectivity is Crucial."

## Highlights

### + Versatility

- Managed platform with dual functions as a switch and an extender
- Dual SFP ports for fiber connectivity
- Dual VDSL2 ports extend data up to 2.2km using legacy copper pair wire

### + Management/Security Features

- Port control
- 802.1x port-based network access control and remote authentication through RADIUS and TACACS+
- Configure and monitor with eVue™ and eLite™

### + Hardened-Grade for Non-Ventilated & Harsh Environments

- Wide operating temperature range -40 to 75°C (-40 to 167°F)
- Fanless operation
- High impact, thermal shock, and electrical noise resistance

### + Support

- Complimentary Technical Support
- Free Firmware Upgrades and notifications
- Limited Lifetime Warranty

## Features

### + Interface

CLI, Telnet, Web GUI

### + Management

Firmware upgrade  
Configuration backup  
DHCP Server/Client  
RMON (Remote Monitoring): group 1, 2, 3, 9  
Port Mirroring  
NTP (Network Time Protocol) synchronization  
LLDP (Link Layer Discovery Protocol)  
IPv4/IPv6  
SNMP v1/v2c/v3

### + Security

MAC Address filtering  
Enable/Disable port  
Storm control  
System logging  
IEEE 802.1x LAN Access control  
Remote authentication through RADIUS and TACACS+  
Complex password support  
Multi-user login and privileged access management  
SSH for CLI and Telnet security  
SSL and HTTPS for web security  
ACL (Access Control List, up to 4096 entries)

### + Quality of Service (QoS)

Priority Queues: 8 queues per port  
Traffic classification based on IEEE 802.1p CoS (Cost of Service), DSCP (Differentiated Services Code Point), WRR (Weighted Round Robin), and strict mode  
Rate Limiting (Ingress/Egress)

### + Layer 2 Features

**Auto-negotiation for port speed and duplex**  
Flow Control  
IEEE 802.3x full duplex mode  
Back-pressure half duplex mode

#### **Redundant Protocols**

IEEE 802.1D STP  
IEEE 802.1w RSTP  
IEEE 802.1s MSTP  
EtherWAN's Alpha-Ring network fault recovery

#### **VLANs**

IEEE 802.1Q Tag VLANs  
GVRP  
GMRP

#### **Link Aggregation**

Static Trunk (4 groups)  
IEEE 802.3ad LACP

#### **IGMP Snooping v1/v2/v3**

### + Switch Properties and Performance

#### **Switching Fabric**

5.6Gbps

#### **Total VLAN Entries**

256 (4096 VID)

#### **MAC Table Size**

8K

#### **Packet Buffer Memory**

2M bits

## Specifications

### + Interface

**Ethernet**

6 x 10/100BASE-TX  
2 x 10/100/1000BASE-T and 100/1000BASE-X SFP  
Combo

**Extender Ports**

2 x RJ11 and Terminal Block Combo  
Cable: 24AWG, 0.5mm diameter, 1 pair

**Console**

1 x DB9

**VDSL Operation**

DIP Switch: Local or Remote

**Alarm Contact**

1 x Relay output, current capacity 1A/24VDC

**LED Indicators**

Per Unit: Power 1, Power 2, Alarm  
Per RJ45 Port: Link/Activity  
Per Extender Port: Link

### + Physical

**Casing Material**

Aluminum

**IP Rating**

IP30

**Dimensions**

73 x 125 x 145mm (W x D x H)  
2.87" x 4.92" x 5.7"

**Weight**

1.25Kg (2.76lbs)

**Installation Type**

DIN-rail (Top Hat Type 35mm)

### + Environmental

**Operating Temp.**

-40 to 75°C (-40 to 167°F)

**Storage Temp.**

-45 to 85°C (-49 to 185°F)

**Relative Humidity**

5% to 95% (non-condensing)

## + Technology

### Standards

IEEE 802.3 10BASE-T  
IEEE 802.3u 100BASE-TX/100BASE-FX  
IEEE 802.3ad link aggregation control  
IEEE 802.3z 1000BASE-SX/1000BASE-LX  
IEEE 802.3x full duplex and flow control  
IEEE 802.1D STP  
IEEE 802.1p QoS  
IEEE 802.1Q Tag VLANs  
IEEE 802.1s MSTP  
IEEE 802.1w RSTP  
IEEE 802.1x PNAC  
IEEE 802.1ab LLDP

### Forward/Filtering Rate

14,800pps for 10Mbps  
148,810pps for 100Mbps  
1,488,100pps for 1000Mbps

### Processing Type

Store-and-forward  
Auto-negotiation  
Half-duplex back-pressure and full-duplex flow control  
Auto MDI/MDIX

## + Power

### Input

12-48VDC Redundant (Terminal block)

### Power Consumption

15.2W Max

### Protection

Reverse Polarity Protection  
Over Current Protection

## + Warranty

### Length

Limited Lifetime

### Details

[www.etherwan.com/support/warranty-policy](http://www.etherwan.com/support/warranty-policy)

## + Regulatory

### ISO

Manufactured in ISO-9001 facility

### EMI

FCC Part 15B Class A  
VCCI Class A  
EN 55032  
EN 61000-6-4  
EN 61000-3-2  
EN 61000-3-3

### EMS

EN 61000-4-2 (ESD)  
EN 61000-4-3 (Radiated RFI)  
EN 61000-4-4 (Burst)  
EN 61000-4-5 (Surge)  
EN 61000-4-6 (Induced RFI)  
EN 61000-4-8 (Magnetic field)

### Safety

UL 61010

### Vibration

IEC 60068-2-6

### Shock

IEC 60068-2-27

### Free Fall

FED STD 101C Method 5007.1

### Industrial

NEMA-TS2

## + What's Included

### Device

Ethernet Switch/Extender


### Cables

1 Console Cable


### Documentation

Quick install guide

# Dimensions



# Application




# Software

Network Management

[eVue™ Network Configuration and Monitoring Tool](#)

Network Discovery

[eLite™ Network Discovery and IP Configuration Tool](#)



**Device List**


| IP             | System Name | Group |
|----------------|-------------|-------|
| 192.168.50.12  | EG99-5012   |       |
| 192.168.50.62  | EX709-5062  |       |
| 192.168.50.254 | R50         |       |
| 192.168.50.11  | EG99-5011   |       |
| 192.168.50.63  | EX74-5063   |       |
| 192.168.50.14  | EX779-5014  |       |
| 192.168.50.61  | EX71v2-5061 |       |
| 192.168.50.44  | EX71-5044   |       |
| 192.168.50.64  | EX73-5064   |       |
| 192.168.50.34  | EX739-5034  |       |

**Topology**

Legend: ● Online ○ Offline ○ Event

**Latest Events**

| Acknowledged | ID   | Severity | Time                   | Service      | Node         | Message                      |
|--------------|------|----------|------------------------|--------------|--------------|------------------------------|
| ✓            | 5107 | Normal   | 6/28/2019, 9:50:35 AM  | login        | server       | User 'admin' logged in.      |
| ✓            | 5106 | Normal   | 6/27/2019, 10:00:50 AM | login        | server       | User 'admin' logged in.      |
| ✓            | 5105 | Major    | 6/24/2019, 1:18:23 PM  | ping-monitor | 192.168.1.19 | Web 192.168.1.19 is down.    |
| ✓            | 5105 | Major    | 6/24/2019, 1:18:23 PM  | ping-monitor | 192.168.1.19 | Teinet 192.168.1.19 is down. |
| ✓            | 5104 | Normal   | 6/24/2019, 1:12:34 PM  | login        | server       | User 'admin' logged in.      |



**eLite**

List Server Firmware Configuration Help

| IP Address    | MAC Address       |
|---------------|-------------------|
| 192.168.50.22 | 00:e0:b3:50:22:00 |
| 192.168.50.31 | 00:e0:b3:50:31:00 |
| 192.168.50.72 | 00:e0:b3:50:72:00 |
| 192.168.50.55 | 00:e0:b3:50:55:00 |
| 192.168.50.23 | 00:e0:b3:50:23:00 |
| 192.168.50.73 | 00:e0:b3:50:73:00 |
| 192.168.50.44 | 00:e0:b3:50:44:00 |
| 192.168.50.64 | 00:e0:b3:50:64:00 |
| 192.168.50.43 | 00:e0:b3:50:43:00 |
| 192.168.50.62 | 00:e0:b3:50:62:00 |
| 192.168.50.71 | 00:e0:b3:50:71:00 |
| 192.168.50.24 | 00:e0:b3:50:24:00 |

Ready

## Ordering Info

### + Model

ED3575-622 6-port 10/100BASE-TX + 2-port 10/100/1000BASE-T / 100/1000BASE SFP Combo + 2-port VDSL2

### + Accessories

|                              |  |
|------------------------------|--|
| Hardened 100BASE SFP Modules | <a href="http://www.etherwan.com/products/sfp-fiber-transceiver">www.etherwan.com/products/sfp-fiber-transceiver</a> |
| Hardened Gigabit SFP Modules | <a href="http://www.etherwan.com/products/sfp-fiber-transceiver">www.etherwan.com/products/sfp-fiber-transceiver</a> |
| DIN-Rail Power Supplies      | <a href="http://www.etherwan.com/products/din-rail-power-supply">www.etherwan.com/products/din-rail-power-supply</a> |

