




EtherWAN

staging-ed9.hellosanta.tw/us/products/ex87000-series **EX87000 Series**

EX87000 Series

Hardened Managed 24-port 10/100BASE and 4-port Gigabit Ethernet Switch with SFP options





Overview

EtherWAN's EX87000 Series provides a hardened fully managed 28-port switching platform combining high performance switching backbone with robust and secure management features required for mission critical and harsh environments where sustained connectivity is crucial.

The EX87000 Series is equipped with 24 fast Ethernet ports, in combination with up to 4 Gigabit, fixed fiber, or SFP combo port options. Mountable on a 1U rack, the EX87000 Series is equipped with EtherWAN's Alpha-Ring self-healing technology, providing less than 15ms fault recovery time making it ideal for applications intolerant to interruption.

Users are able to access management features such as port security, IGMP snooping, VLANs, GARP protocols, and LACP via web browser, Telnet, SNMP, RMON, TFTP, and RS-232 console interfaces. The EX87000 allows GOOSE messages to be passed through without modifying the frame contents.

With its IEC 61850-3 and IEEE 1613 certified for power substations, EN 50121-4 certified for railway applications, and NEMA-TS2 certification for traffic applications, the EX87000 Series is capable of operating under high EMI environments at the temperatures ranging from -40 to 75°C (-40 to 167°F), making it an ideal choice for harsh environment applications.

EtherWAN — "When Connectivity is Crucial."

Spotlight

Versatile Connectivity

- Provides flexibility of 24-port 10/100BASE-TX/FX/BX/SFP plus 4-port Gigabit-TX/SX/LX/BX/SFP

Hardened Grade

- Wide operating temperature range for extreme environments
 - Fanless and ruggedized housing
 - High shock and electric noise immunity

KEMA-Certified

- IEC 61850-3 and IEEE 1613 performance tests conducted by KEMA

Features

Interface

- CLI, Telnet and Web Browser
- SNMP v1/v2c/v3

Management

- Firmware and configuration upgrade and backup via TFTP
- Supports DHCP Server/Client
- RMON (Remote Monitoring)
- Port mirroring: TX/RX and both
- NTP (Network Time Protocol) time synchronization
- IEEE 802.1ab LLDP (Link Layer Discovery Protocol)
- IPv4/IPv6

Security

- MAC address filtering
- Enable/Disable port
- Storm control (Broadcast and multicast types)
- IEEE 802.1x LAN access control
- Remote authentication through RADIUS and TACACS+
- SSHv1/v2 for CLI and Telnet security
- SSL for web security
- ACL
- Multi-level user account/password against unauthorized configuration

Quality of Service (QoS)

- Priority Queues: 4 queues per port
- Traffic classification based on IEEE 802.1p CoS, DSCP, WRR (Weighted Round Robin) and strict mode
- Rate Limiting (Ingress/Egress)

Layer 2 Features

- **Auto-negotiation for port speed and duplex**
- Flow Control
- IEEE 802.3x full duplex mode
- Back-pressure half duplex mode
- **Redundant Protocol**
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- EtherWAN's Alpha-Ring network fault recovery (<15ms) and Alpha-Chain
- **VLANs**
- IEEE 802.1Q Tag VLANs (128 groups, 4096 VID)
- GVRP (GARP VLAN Registration Protocol)
- GMRP (GARP Multicast Registration Protocol)
- **Link Aggregation**
- Static Trunk (8 groups, support MAC base)
- IEEE 802.3ad Link Aggregation Control Protocol

Specifications

Technology

- **Standards**

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX/100BASE-FX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-SX/1000BASE-LX
- IEEE 802.3x Full duplex and flow control
- IEEE 802.1p QoS
- IEEE 802.1Q Tag VLANs
- IEEE 802.1w RSTP
- IEEE 802.1x Port-based Network Access Control

- **Forward and Filtering Rate**

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps
- 1,488,100pps for 1000Mbps

- **Packet Buffer Memory**

- 12M bits

- **Processing Type**

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure and IEEE 802.3x full-duplex flow control
- Auto MDI/MDIX

- **Address Table Size**

- 16K MAC addresses

Interface

- **Ethernet Port**

- 10/100BASE-TX: 0, 8, 16 or 24 ports
- 100BASE-FX: 0, 8, 16 or 24 ports
- Gigabit: 4 ports

- **Console Port**

- One DB9 RS-232 port

- **Alarm Contact**

- One relay output with current 0.6A/30VDC

- **LED Indicators**

- Per Unit: Power 1, Power 2, Alarm
- Per Port: Link/Activity (Green)
- Per SFP Slot: Selected (Green)

Environment

- **Operating Temperature**

- -40 to 75°C (-40 to 167°F)
- Tested @ -40 to 85°C (-40 to 185°F)

- **Storage Temperature**

- -45 to 85°C (-49 to 185°F)

- **Ambient Relative Humidity**

Power

- **Input**

- Power input can be configured as:
 - • ±48VDC (Terminal Block)
 - • 88-300VDC or 100-240VAC (Terminal Block)
 - • 100–240VAC (AC Inlet)

- **Power Consumption**

- For models with all copper ports: EX87604 Series: 21.9W@230VAC
- For models with all fiber ports: EX87064 Series: 40.6W@230VAC

Mechanical

- **Casing**

- Metal Case
- IP30

- **Dimensions**

- 442 x 375 x 44mm (W x D x H)
(17.4" x 14.7" x 1.73")

- **Weight**

- 5Kg (11lbs.)

- **Installation**

- Rack mounting

Regulatory Approvals

- **ISO**

- Manufactured in an ISO 9001 facility

- **Safety**

- • UL 62368

- **EMI**

- • FCC Part 15B Class A
- • EN 61000-6-4

- **EMS**

- • EN 61000-6-2
- • EN 61000-4-2 (ESD Standards)
- • EN 61000-4-3 (Radiated RFI Standards)
- • EN 61000-4-4 (Burst Standards)
- • EN 61000-4-5 (Surge Standards)
- • EN 61000-4-6 (Induced RFI Standards)
- • EN 61000-4-8 (Magnetic Field Standards)
- • IEC 61000-4-10 (Oscillatory wave magnetic field test)
- • IEC 61000-4-16 (Power frequency immunity test)

- **Environmental Test Compliance**

- • IEC 60068-2-6 Fc (Vibration Resistance)
- • IEC 60068-2-27 Ea (Shock)
- • FED STD 101C Method 5007.1 (Free fall w/package)

- **Industrial Compliance**

- • IEC 61850-3/IEEE 1613

EX87244-WXYZ

8-port 10/100BASE-TX +16-port 100BASE-FX +4-port Gigabit Hardened Managed Ethernet Switch

EX87064-WXYZ

24-port 100BASE-FX +4-port Gigabit Hardened Managed Ethernet Switch

EX87064-V0VZ

24-port 100BASE-SFP +4-port Gigabit SFP Combo Hardened Managed Ethernet Switch

* Rack mounting kit included.

100FX Fiber Options (W)

1

Multi Mode (SC) - 2Km

2

Multi Mode (ST) - 2Km

A

Single Mode (SC) - 20Km

H

Single Mode (ST) - 20Km

P

Single Mode (SC) WDM-TX: 1310nm/RX: 1550nm-20Km

Q

Single Mode (SC) WDM-TX: 1550nm/RX: 1310nm-20Km

V

100BASE SFP

* More 100FX Fiber options also available upon request.

Numbers of fixed Gigabit Fiber (X)

0

None

4

Four Gigabit Fiber Ports

Gigabit Port Options (Y)

3

1000BASE-SX (SC) - 550m

4

1000BASE-SX (SC) - 2Km

A

1000BASE-LX (SC) - 10Km

B

1000BASE-LX (SC) - 20Km

R

1000BASE-BX (SC) WDM-TX: 1310nm/RX: 1550nm-20Km

S

1000BASE-BX (SC) WDM-TX: 1550nm/RX: 1310nm-20Km

V

4-port 100/1000BASE SFP Combo with 10/100/1000BASE-TX

* More Gigabit options also available upon request.

Power Input Interface (Z)

TR

±48VDC Redundant (Terminal Block)

WR

88-300VDC or 100-240VAC Redundant (Terminal Block)

CR

100-240VAC Redundant (AC Inlet)

